

AUTOMATIC + DEXRON III-H

Last edition:
07/03/2024

KENNOL AUTOMATIC + DEXRON III H is a fully synthetic oil developed for automatic gearboxes, power steerings and other equipment for which a DEXRON III H type fluid is recommended.

SPECIFICATIONS

AINSI WARNER JWS 3309 / JWS 3324
ALLISON TES-228, C-4
AUDI / VW G052162A1/A2 / G055005A1/A2/A6 / G055025A2 / G052162 / G052990
BMW 7045E / ETL-8072B
DAEWOO LT 71141
DAIHATSU ALUMIX ATF D-II, D-III SP
DEXRON II-E / III-G / III-H
FORD WSS M2C-138CJ / 166H / 202B / 922A1 / 924A / MERCON V
HONDA ATF Z1 / DW1
HYUNDAI / KIA SP-II / SP-III / SP-IV
JAGUAR ATF 3403 M115
JASO M315 TYPE1A/2A
MAN 339 TYPE Z3/V2
MAZDA ATF M-V / FZ / F1 / S1 / N1
MB 236.1 / 236.2 / 236.3 / 236.5 / 236.6 / 236.7 / 236.8 / 236.9
MITSUBISHI SK / SP-II / SP-III / AW / J2 / J3
NISSAN MATIC FLUID C/D/J/K/S
RENAULT SAMSUNG SAFT-D
SUBARU ATF / AFT SAT
SUZUKI ATF5006 / 2326 / 2384K / 3314 / 3317
TEXACO 7045-E / 8072B / N402
TOYOTA TYPE D-II / D-III / T-III / T-IV / WS
VOITH 55.6335 G607
VOLVO CE97340 / 97325 / 97335
ZF TE-ML 03D / 04D / 09 / 11B / 14A / 14B / 14C / 16L / 17C / 21L

PROPERTIES

Anti-wear properties and shearing stability	→ Optimal performance over time Extends the shelf life of transmissions
"New generation" additives	→ Excellent resistance to oxidation

https://www.kennol.com/EN/FT/KENNOL_AUTOMATIC_PLUS_DEXRON_III_H_EN.pdf

